

TECHNICAL
SPECIFICATIONS

Product Code	PM040-MI43-SCH
Dimension (mm) W x L x H	50x50x7
Material	PMMA
Fastening	Screw
Beam Angle	40°
Type	12 in 1
Optical Efficiency	%93
Rohs Complaint	Yes


MATERIALS

PMMA clear, Non-yellowing for 10 years.
Yellowness Index (YI) according to the test standarts for Arizona/Florida outdoor exposure testing:
-YI 6 under hot/dry conditions
-YI 8 under hot/wet conditions


INSTRUCTIONS FOR USE &
MAINTENANCE

Working Temperature : -40° C ~ +100° C
Storage Temperature : -40° C ~ +100° C
Please handle or install lenses with wearing gloves.
Skin oils may damage lens or its optical characteristic.
Never use any commercial cleaning solvents on lenses , like alcohol.
If necessary, clean lenses wiht mild soap, water and soft cloth.


OSRAM DURIS S5




LUXEON 3030 2D




SEOUL MJT 3030




NICHIA NF2W 757 GR






CREE J SERIES



SAMSUNG LM302Z+





	UNIT mm	PART NO: PM040-MI43-SCH	 GENERAL TOLERANCES ± 0,2 MM	
	MATERIAL	PMMA	REV.	REVISION
	WEIGHT	8,97 g	1	
	DATE	22.06.2020	2	
		PAGE 1 / 1	3	REV. DATE
			FORM	A4 SCALE 1:1

Box Size (mm) W x L x H	370x300x225
Box Weight	7,2 Kg
Box Quantity	660 pcs

